

15inch & 17inch Display



White

AerPOS is also offered with an optional white chassis. The exterior of the aluminum is finished with a glossy smooth coating.



Slim

Both the 15inch and 17inch displays measure less than 4 centimeters in thickness.



be **COLORFUL**

Color can be more than a tint, tone and hue. It can express a feeling, make a statement and show a personality. By special request, we have customized different colors for many different businesses.



Modular Design

Components and peripherals have been designed so that they can be installed or removed under 1 minute. The modular design of AerPOS models ensures high serviceability and reliability.



Add-on Devices

There are multiple add-on devices that are available for AerPOS. There are single function devices such as MSR reader, iButton reader, fingerprint reader and RFID reader. There are also 2in1 devices that combine the MSR reader with an iButton, Fingerprint or RFID reader.

Customer Display

Choose between a pole type and non-pole type customer display. There is a between Liquid Crystal Display (LCD) with LED backlight and Vacuum Fluorescent Display (VFD). Each model allows for easy programming with escape sequence commands and features adjustable display height, display swivel and tilt.



2nd Display

Enhance the customer experience by showing the latest store promotion and other relevant information at the checkout. Choose between an 11inch and 15inch display.



MODEL NO.	AP-3615	AP-3617
Processor	Intel® Celeron® G540, 2.5Ghz Intel® Core i3-2120, 3.3Ghz Intel® Core i5-3550S, 3.0Ghz	
System Memory	2GB Standard, Maximum 8GB (1x204-pin DDR3)	
Power Supply	150W (12V / 12.5A) External Power Adaptor	
Storage Device	1 x 2.5" SATA HDD or SSD	
Graphics	Intel® H61	
Speaker	Internal Speaker 2W x 2	
Construction	Aluminum Die-casting + Plastic + Glass	
Housing Color	Black with Silver Trim Black with Red Trim White with Silver Trim	
Smart Management	Smart Management 2.0 Standard	
Touch LCD Display		
Size / Resolution	15" TFT-LCD / 1024 X 768	17" TFT-LCD / 1280 X 1024
Brightness (Backlight Type) & Touch Screen	350 cd/m2 (LED); 5-Wire Resistive Touch / Projected Capacitive Touch	250 cd/m2 (LED); 5-Wire Resistive Touch / Projected Capacitive Touch 350 cd/m2 (LED); 5-Wire Resistive Touch / Projected Capacitive Touch
I/O Ports		
Serial Port	4 x External: COM 1, COM 2 (DB9), COM 3, COM 4 (RJ45)	
USB Port	5 x External (4 Rear + 1 Side)	
Cash Drawer Port	1 x RJ11 (12V)	
LAN Port	1 x RJ45 Gigabit LAN	
Audio Port	1 x Line Out, 1 x Mic In	

Video Port	1 x VGA	
DC Input	1 x 12V DC Jack 2.5 mm	
Optional I/O Ports		
Type A	Serial Port: COMA (DB9); 12V Powered USB Port x 1; 2 x USB	
Type B	Powered USB Port: 24V x 1	
Type C	Powered USB Port: 24V x 1; 12V x 2	
OS Supported		
Windows	Windows XP, POSReady 2009, Windows 7, POSReady 7, Windows 10 Enterprise	
Dimensions & Weight		
Product (W x H x D)	370 x 360 x 235 mm, 7.1 Kg	410 x 386 x 235 mm, 10 Kg
Carton (W x H x D)	480 x 460 x 320 mm, 9.1 Kg	560 x 540 x 360 mm, 11 Kg

+ LEGACY
+ ADD-ON DEVICES
+ CASH DRAWERS
+ CUSTOMER DISPLAYS
+ PRINTERS